

Industrial Specification Grade 15A Locking Receptacles

2-Pole, 3-Wire Grounding; 3-Pole, 3-Wire Non-Grounding; 3-Pole, 4-Wire Grounding; 4-Pole, 4-Wire Non-Grounding; 4-Pole, 5-Wire Grounding

	Device Type	15A Hart-Lock™ Single Receptacles: NEMA L5-15, L6-15, L7-15	15A Hart-Lock™ Duplex Receptacles: NEMA L5-15, L6-15, L7-15	15A Hart-Lock™ Single & Duplex Receptacles: Non-NEMA 10/15A	15A Hart-Lock™ Isolated Ground Single & Duplex Receptacles: NEMA L5-15, L6-15
	Wiring Type	Back & side wire	Back & side wire	Back & side wire	Back & side wire
	Testing & Code Compliance	<ul style="list-style-type: none"> Listed to UL 498 , file no. 2369 UL verified to Federal Spec. WC-596G, except CWL515R CSA certified to C22.2, no. 42 	<ul style="list-style-type: none"> Listed to UL 498 , file no. 2369 UL verified to Federal Spec. WC-596G CSA certified to C22.2, no. 42 	<ul style="list-style-type: none"> UL recognized component, file no. E2369 	<ul style="list-style-type: none"> Listed to UL 498 , file no. 2369 CSA certified to C22.2, no. 42, except IGL615R
Specifications: Environmental	Flammability	Meets UL 94 requirements, V0 rated	Meets UL 94 requirements, V0 rated	Meets UL94 requirements, V0 rated	Meets UL 94 requirements, V0 rated
	Temperature Rating	-40°C to 115°C (-40°F to 239°F)	-40°C to 115°C (-40°F to 239°F)	-40°C to 115°C (-40°F to 239°F)	-40°C to 115°C (-40°F to 239°F)
Specifications: Electrical	Dielectric Voltage	Withstands 2500V per UL 498	Withstands 2500V per UL 498	Withstands 2500V per UL 498	Single: withstands 2500V per UL 498 Duplex: withstands 1500V per UL 500
	Current Interrupting	Yes, at full-rated current	Yes, at full-rated current	Yes, at full-rated current	Yes, at full-rated current
	Temperature Rise	Max. 30°C (86°F) after 150 cycles of overload @ 200% of rated current (DC)	Max. 30°C (86°F) after 150 cycles of overload @ 200% of rated current (DC)	Max. 30°C (86°F) after 150 cycles of overload @ 200% of rated current (DC)	Max. 30°C (86°F) after 100 cycles of overload @ 150% of rated current (DC)
Specifications: Mechanical	Terminal Accommodation	#14 - #10 AWG	#14 - #10 AWG	#14 - #10 AWG	#14 - #10 AWG
	Voltage Ratings	Permanently marked on device	Permanently marked on device	Permanently marked on device	Permanently marked on device
Materials:	Face	Glass-filled nylon	Glass-filled nylon	Glass-filled nylon	Glass-filled nylon
	Base	Glass-filled nylon	Glass-filled nylon	Glass-filled nylon	Glass-filled nylon
	Mounting Strap	.050" thick pre-plated steel	.050" thick pre-plated steel	.050" thick pre-plated steel	.050" thick pre-plated steel
	Auto Ground Clip	N/A	Yes	Yes	Yes
	Line Contacts	0.032" thick brass	0.032" thick brass	0.032" thick brass	0.036" thick brass
	Terminal Screws	#8-32 steel screws, nickel plated	#8-32 steel screws, nickel plated	#8-32 steel screws, nickel plated	#8-32 steel screws, nickel plated
	Ground Screw	#8-32 brass screw, green	#8-32 brass screw, green	#8-32 brass screw, green	#8-32 brass screw, green
	Mounting Screws	Steel, zinc-plated	Steel, zinc-plated	Steel, zinc-plated	Steel, zinc-plated